



MARINE CUBE SPEAKERS

MS-BX225

SPECIFICATIONS

MAX POWER RATING	100 Watts
RMS POWER INPUT	35 Watts
EFFICIENCY (1W/1M)	86dB
FREQUENCY RESPONSE	120Hz – 22kHz
IMPEDANCE	4 Ohms
DIMENSIONS	
WITHOUT BRACKET	Depth 120mm - 4 3/4"
	Width 85mm - 3 3/8"
	Height 175mm - 6 7/8"
WITH BRACKET	Depth 128mm - 5"
	Width 85mm - 3 3/8"
	Height 190mm - 7 1/2"



N.B. Mesh grilles can be removed for logo repositioning purposes.

PRODUCT CONTENTS

- 2 x Dual Cube Speakers
- 2 x Mounting Brackets
- 2 x Mounting Knobs
- 2 x 8 Meter Speaker Cables
- Manual
- Warranty Card

INSTALLATION

- » Check mounting position for adequate space (see caution below).
- » Place the mounting bracket in position, then mark and drill the mounting holes.
- » Place mounting knob in bracket.
- » Mount bracket with appropriate screws (Not Supplied).
- » Connect the wires from the source to the Cube speaker ensuring the correct polarity is observed.
- » Attach the Cube speaker to the bracket using the mounting knob supplied.
- » Adjust the positions of the dual cube system to the preferred position before tightening the mounting knobs.

RECORD YOUR PURCHASE DETAILS HERE:

MODEL NUMBER

DATE OF PURCHASE

AFFIX RECEIPT HERE

CAUTION: Speakers can cause interference to navigational equipment. Please refer to navigation equipment manufacturer for speaker mounting restrictions.
WARNING! Audio Systems can produce sound levels over 135dB. Continuous exposure to sound pressure levels over 100dB may cause permanent hearing loss!

.....
www.fusionelectronics.com



PUBLISHED BY FUSION ELECTRONICS LIMITED. © Copyright 2009 by FUSION Electronics Limited. All rights reserved. Specifications and design are subject to change without notice.
 YOU CAN HELP PROTECT THE ENVIRONMENT! Please remember to respect the local regulations: Hand in the non-working electrical equipment to an appropriate waste disposal center.